

S9500-22XST DISAGGREGATED CELL SITE GATEWAY ROUTER

The UfiSpace S9500-22XST is a high-performance, versatile open networking white box router that is designed to address the changing needs of backhaul transport requirements as Telecoms make the transition from legacy technologies towards 5G. It enables telecoms and service providers to deploy disaggregated open network infrastructure to lower costs and rapidly scale existing services for edge computing, mobile backhaul, and broadband access applications.

The S9500-22XST is future-proofed with a powerful quad-core processor, 22 high-speed interfaces and full timing features supporting IEEE 1588v2 and SyncE. It is suitable for both indoor and outdoor deployments with redundant, hot-swappable components for convenience, increased availability, reliability and lower costs of maintenance.

KEY FEATURES

- Supports full SyncE and IEEE 1588v2 (T-GM, T-BC, T-TC and T-TSC)
- Integrated Stratum 3E OCXO with optional hold over performances
- Class C timing accuracy support
- Internal GNSS receiver for master clock implementations
- Rich timing interfaces: ToD, 1PPS, BITS and 10MHz
- 2GB deep buffering
- Supports 100M/1G for legacy, 10G/25G for 5G and up to 100G for backhaul
- Individual BMC allowing automatic and remote operations for monitoring and managing platform health status
- 1 RU small form factor with 302mm depth
- Hot swappable power supplies with 1+1 redundancy support
- Hot swappable fan modules with 2+1 redundancy support

KEY BENEFITS

- Compatible with open networking standards for highly reliable, composable networks.
- Future-proof for 5G with ultra-low forwarding latency, high precision frequency and phase timing synchronizations.
- Temperature hardened design to offer more flexibility when deploying outside plant cabinets for cell site backhuls.
- Suitable for WAN and long-haul applications, designed for up to 80km backhaul distances.



SPECIFICATIONS

PHYSICAL

♦ 2 x 40/100G QSFP28 ports	
♦ 8 x 1/10/25G SFP28 ports	
♦ 8 x 100M/1/10G SFP+ ports	
♦ 4 x 100M/1G RJ45 ports	
♦ 1 x RJ45 & Micro USB serial console port	
♦ 1 x 100/1000M RJ45 management port	
♦ 1 x USB 2.0 Type-A port	
Processor	Intel Broadwell-DE 4-Core @ 1.5GHz
Memory	8GB DDR4 (Up to 32GB)
Storage	32GB SSD (Up to 128GB)
ASIC	Broadcom Qumran-AX BCM88470
BMC	AST2400
Timing	1 x GNSS input SMA
Interfaces	1 x 1PPS input/output SMA
	1 x 10MHz input/output SMA
	1 x ToD input RJ45
	1 x BITS input RJ48
Timing Support	Stratum 3E OCOXO ITU-T Synchronous Ethernet (SyncE) IEEE 1588v2 - Default, G.8275.1, G.8275.2, SMPTE ST 2059-2** , T-GM, T-BC/OC, T-TC
Chassis (WxDxH)	1 RU, 440 x 302 x 43.5 mm or 17.32" x 11.89" x 1.713" Weight: 4.75kg or 10.47lb (without FRU)
Redundancy	Hot swappable, 1+1 redundant PSU Hot swappable, 2+1 redundant Fans

*NOS integration is necessary to activate the specific feature.
**Additional license is required

S9500-22XST

Telecom
Networking
Solutions

ENVIRONMENTAL

Power Specs.	AC input: 100 to 240V, 3A
	DC input: -36 to -75V, 8A
	Typical power: 111.8 Watts (no transceiver)
Max. Operating Specs.	Operating temperature: -40°C to 65°C (-40°F to 149°F) Operating humidity: 5% to 85% (RH), non-condensing
Max. Non-Operating Specs.	Storage temperature: -40°C to 70°C (-40°F to 158°F) Storage humidity: 5% to 93% (RH), non-condensing

PERFORMANCE

Switching Capacity	300Gbps
Deep Buffer	2GB

REGULATORY COMPLIANCE

Safety	UL 62368-1	EMC	FCC Part 15, Subpart B, Class A
	IEC 60950-1		ICES-003, Class A
	IEC 62368-1		EN 55032, Class A
	BSMI		EN 55024
Environment	RoHS WEEE		EN 55035
			EN 62479
			EN 50663
			EN 300 386
			EN 301 489
			EN 303 413
		BSMI	VCCI CISPR 32, Class A

Specifications are subject to change without notice.
Contact our sales team for current configuration options.

S9500-22XST Front and Back Views



ACCESSORIES

Compatible Transceiver Types	100G QSFP28 SR4, 100G QSFP28 LR4, 100G QSFP28 ER4, 25G SFP28 SR, 25G SFP28 LR, 25G SFP28 ER, 10G SFP+ SR, 10G SFP+ LR, 10G SFP+ ER, 10G SFP+ ZR, 1G SFP SX, 1G SFP LX, 1G SFP EX, 1G SFP ZX
	Compatible Timing Cable Types
50 ohms SMA coaxial cable with 1/4-36UNS-2B connector for GNSS, 1PPS, and 10MHz	
Shield cable with RJ45 for ToD	
Shield cable with RJ48 for BITS	
Available to Order	
Power Supply Types	
PSU-201-DISB, 200W DC, intake air flow	
PSU-201-AISB, 200W AC, intake air flow	
Fan Types	
FAN-402825-HD, exhaust air flow	

